



### Показатели деятельности

- | API: SN/CF
- | ACEA: A3/B4
- | VW 502.00 / 505.00
- | MB 229.3 / 226.5
- | BMW: Longlife-01
- | OPEL GM-LL-B-25
- | RENAULT 0700

## SYNTH-SX 5W30

This is a full synthetic lubricant based on carefully selected very high quality base oils, providing outstanding wear and sludge protection, even under the most severe driving conditions. Due to its enhanced frictional properties, improved fuel economy is obtained.



### Приложения

This motor oil has been specially designed to meet the latest requirements for most American and Asian passenger cars, SUV's and light vans. Originally intended for fuel-injected gasoline engines, including turbo-charging and multi-valves, it can also be used in light duty diesel engines without particulate filters.

### Характеристики

	Unit	Average Value
Плотность при 15 °C	kg/l	0.856
Вязкость при 40 °C	mm <sup>2</sup> /s	64.3
Вязкость при 100 °C	mm <sup>2</sup> /s	10.9
Вязкость при минус 30 °C	mPas	6300
Коэффициент вязкости		162
Температура вспышки по Кливленду	°C	228
Температура застывания	°C	-45
Общее щелочное число	mgKOH/g	8.1
Содержание сульфатной золы	%	0.88

### Упаковка

